# The Application of the NeXus Format to Muon Data

<u>Steve Cottrell</u> and Freddie Akeroyd STFC, ISIS Facility, RAL, UK



Or ...

# A Common Format for Muon Data

Not the same thing ...

but perhaps the two things have become confused!



## Outline

- The World of Muons
- A NeXus Definition for ISIS Muons
  - An early adopter
  - Where 'we' went wrong
  - The need for a new Version
- The way forward



# But avoiding a detailed description of the Instrument Definition!

### Latest Version can be Read at:

http://www.nexusformat.org/Muon Time Differential



## The World of Muons




# Different to Neutrons and X-rays

## Muons ...

Travel in a beamline from target to sample

Stop in the sample





Detect muon decay products




Generate lots of 'small' data files:

<100 detectors ⇒
~1Mbyte/run,
5-60mins/run



## Four User Facilities



- Complementary ... Users work between facilities
- ~10% size of Neutron Community



## A Common Data Format?



Physica B 289-290 (2000) 722



Towards a single µSR data format and common high quality user-facility analysis software

T.M. Riseman\*

School of Physics and Astronomy, University of Birmingham, Birmingham B15 2TT, UK

This round table discussion considered coordinating improvements in the portability and quality of µSR analysi software, Panel members were Tanya Riseman, Ivan D. Reid (PSI), Steve P. Cottrell (ISIS), Jess H. Brewer (TRIUMF) and Mark Koennecke (PSI); Mark is a developer of the new neutron and X-ray scattering data format NeXus. © 200 Elsevier Science B.V. All rights reserved.

Keywords: Data formats, Future development

The round table panel members and audience considered two basic tactics. The first is to move towards a universal data format for all facilities. This might provide indirect improvement in software, because it will be much easier for both facility and 'private' software to be used with data from different facilities, with the better programs gaining more users. The second tactic is to concentrate on directly improving the analysis software.

For immediate hardware reasons, the first tactic was selected. Many of the new time-to-digital converters are incompatible with all pre-existing data formats. Data formats at PSI, ISIS and KEK are both archaic and extremely difficult to adapt to operating systems other than VMS, which is being phased out

Mark Koennecke discussed how NeXus was chosen by the neutron scattering community: (see www.neutron.anl.gov/NeXus/NeXus\_intro.html).

E-mail address: tmr@th.ph.bham.ac.uk (T.M. Riseman).

NeXus is a data object/file definition in Hierarchical Data Format (HDF), which is a widely used, multi-platform, public domain data format.

The MUon Data (MUD) format presently used at TRIUMF is also a hierarchical data format, but implemented in C with FORTRAN bindings; (see http://musr.physics.ubc.ca/mud/).

Adaptations of NeXus and MUD are two obvious candidates for a universal µSR data format. In favor of MUD, it is already in use at TRIUMF and is simple. In favor of NeXus, it is being actively developed at PSI and ISIS for the neutron community, and software such as HDF browsers and Open Genie already exist.

A data format task force was formed: Jess H. Brewer (TRIUMF), Steve P. Cottrell (ISIS), Wataru Higemato (KEK), Ivan D. Reid (PSI), and Tanya M. Riseman (Univ. of Birmingham). A web site has been set up with a long write-up of the round table, the results of the round table's µSR user survey and on-going discussion (http://musr.physics.ubc.ca/fmts/).

- Idea of a common data format was discussed at the 1999 µSR conference
- PSI and ISIS formats archaic
- Existing MUD format and NeXus discussed
- Common Exchange Format?
- Data format task force formed
- Encouraged by the ISMS

0921-4526/00/\$- see front matter © 2000 Elsevier Science B.V. All rights reserved PII: S0921-4526(00)00334-3

But little progress ... why?



<sup>\*</sup>Fax: + 44-121-414-4719.


# A NeXus Instrument Definition for ISIS Muons



## ISIS Muons ... an early adopter

### **Student project:**

•Instrument Definition (RAL-TR-2001-029)



#### Later:

Move from VMS to a PC-based DAE meant a new data format

NeXus was the obvious choice

Now have >65000 NeXus files!

- File converter (MCS→NeXus)
- Read routines
- Analysis programs


• . . .




## **Analysis Tools**

Using NeXus (and HDF) gave us access to lots of analysis tools:


Muon Specific ...






and Generic ...











## Where 'we' went wrong ...

- I got some things wrong when writing the Definition
- NIAC evolved aspects of the NeXus recommendations (the Muon Definition preceded NIAC)
- Need to be closer to the ISIS Neutron Definition to simplify support for both DAE and analysis codes
- The Definition needed to be better able to adapt to new experiments and other muon sources



## A New Instrument Definition

Needed to answer these criticisms

Latest version at:

http://www.nexusformat.org/Muon Time Differential

Not yet ratified, but getting close!

Improvements?



## Improved Metadata

### Description of the muon beamline (for instance)

#### muon\_beamline

RE	Name	Attribute	Туре	Va	Value		Description		
	NV concetion								
1	beamline		NX CHAR				nam	ie	
0/1+	diagnostics		NXdiagnostics				cont	tainer for any	$\top$
							bear	nline diagnostic rmation.	
0/1+	{beamline		NXdipole_magn					nline components	#
0/11	component}		et		RE	Name	Ocai	Attribute	7
	component;		NXquadrupole_ magnet			NXelectrost kicker	atic_		

Few entries are required, more can be added without breaking the format

0/1	diagnostics	5			container for any			
					beamline diagnostic			
					information.			
0/1+	{beamline	NXdipole_magn			beamline components  Attribute		1	
	component}	et	RE			Туре	Value	Description
		NXquadrupole		NXelectrostat	ric_			component name
		magnet   magnet		kicker				
		NXsolenoid ma	1	description		NX_CHAR		name
		gnet	0/1	source_distan	ce	NX_FLOAT		distance of flight path
		NIVI						from production target
		NXseparator	0/1		units	NX_CHAR	'metres'	
		NXspinrotator	0/1	timing		NX_FLOAT		kicker timing, as
		NXbeamline col						defined by
		limator						'description' attribute
		NXseptum_mag	0/1		units	NX CHAR	'nano.second'	•
		net	0/1		description	NX CHAR		
		NXsteering_mag	0/1	set voltage		NX FLOAT		set value on PS
		net net	0/1		units	NX_CHAR		
-		net .	0/1	read_voltage		NXlog		read from PS
			0/1		units	NX_CHAR		
			0/1	set current		NX FLOAT		set value on PS
			0/1		units	NX_CHAR		
			0/1	read_currente		NXlog		read from PS
			0/1		units	NX CHAR		

electrostatic\_separator

Metadata designed to link with beam simulation, e.g. TURTLE or GEANT



# Improved support for diagnostics

i.e. To determine where the experiment went wrong!

Easy to log and store parameters ... more metadata

#### runlogs (NXcollection)

RE	Name	Attribute	Type	Value	Description			
	NXcollection							
To contain action and acquisition logs arising from activities of the data acquisition electronics (DAE) during the								
run – entries will be facility specific.								

#### selogs (NXcollection)

RE	Name	Attribute	Type	Value	Description				
	NXcollection								
To cor	To contain sample environment logs arising from activities of the experiment control software – entries will be								
facility	facility specific.								

### **Container classes**:

runlogs: e.g. run start/stop, errors, etc selogs: e.g. temperature, field vs. time

(NXlog's)

NXlog extended to log arrays



# Guidance for extending Definiton

Increasingly ... Experiments = 'Muons' + 'x', where 'x' might by 'Light', 'E field', 'RF field', 'Humidity', ...

Can't define everything, so we've made recommendations

RE	Name	Attribute	Туре	Value	Description
	rf_frequency		NX_FLOAT32	rf frquency	
		units	NX_CHAR	'MHz'	
		hardware	NX_CHAR	'marconi'	
		display_name	NX_CHAR	name displayed on	at, typically SECI
				DAE software	block name
		software	NX_CHAR	version of driver used	at, typically VI name
				to collect data	and version
	rf_delay		NX_FLOAT32	rf delay	relative to extract
		units	NX_CHAR	'us'	
		hardware	NX_CHAR	'stanford'	
		display_name	NX_CHAR	name displayed on	at, typically SECI
				DAE software	block name
		software	NX_CHAR	version of driver used	at, typically VI name
				to collect data	and version

Define new entries (example for RF)

and location in file (e.g. selogs)

Naming convention using prefix



## Improved Multi-period Support


#### 1 Stimulus ... 2 Periods

'RF on'
Memory 1

Switch every 'n' pulses

'RF off'
Memory 2

Twice as much data!



Store information about periods, Link information from NXdata



# The Way Forward



# Why not a Common Format?

- Other Facilities perhaps lacked the motivation:
  - Happy with current formats (scientists see no benefit)
  - Moving to NeXus is resource intensive
  - Data formats are not that exciting!
- Revision of the ISIS Definition might have created doubt (in Muons) that NeXus is a useful standard:
  - NIAC needs to be cautious proposing changes to existing class definitions don't break what's in place.
  - Need a balance: set the Definition quickly and carefully, but then don't touch it!
- Decisions, decisions:
  - Everyone has their own idea for the format!
  - Idea overload and disappointment



# But it's not all gloom!

- Revision of the Instrument Definition has been painful, but we've nearly finished ... then no more changes!
- EU Framework Programme 7 (under the Neutron and Muon I3) is stimulating EU wide adoption of NeXus (PSI and ISIS are close to agreeing a Definition)

'A detailed Nexus instrument definition file will be devised, suitable for both ISIS and PSI, which is suitable for capturing all instrument and beam parameters typically required for beam simulation.'

 Advanced instruments and analysis techniques
 (e.g. beam and instrument simulation) require better metadata – perhaps a compelling reason to switch?



## Conclusion

Idea for a **Common Data Format** 

Can we close the loop?

Stimulated

## **Muon Instrument Definition**

(already useful to ISIS)



## Acknowledgements

- Thanks to Damian Flannery and Freddie Akeroyd who have done most of the coding, and Freddie for a lot of input to the new version of the Instrument Definition.
- Thanks to continued funding by the European Union under Framework Programmes 6 and 7 - enabling PSI and ISIS to work together on this project

#### **Useful links:**

http://www.nexusformat.org/Muon Time Differential

http://muons.neutron-eu.net/MuonsHome/

